



MONTANARO F. L L I SRL

Officina Macchine Enologiche

Via Cav. Ottavio Riccadonna, 218 - 14053 – CANELLI (AT)

Tel. E Fax. +39 0141 823611

E-mail: info@montanarofratelli.com

Internet: www.montanarofratelli.com

COD. FISCALE E P. IVA 01429500059
NR. REG. IMPR CC.I.AA AT: 01429500059

RIEMPITRICE BAG IN BOX SEMIAUTOMATICA





MONTANARO F. L L I SRL

Officina Macchine Enologiche

Via Cav. Ottavio Riccadonna, 218 - 14053 – CANELLI (AT)

Tel. E Fax. +39 0141 823611

E-mail: info@montanarofratelli.com

Internet: www.montanarofratelli.com

COD. FISCALE E P. IVA 01429500059

NR. REG. IMPR CC.I.AA AT: 01429500059



Programmazione automatica e memorizzazione dei volumi di riempimento tramite display con pannello di comando digitale "touch screen", con la possibilità di salvare i programmi di riempimento.

- Contalitri elettromagnetico Burkert.
- Possibilità di riempimento sacchetto flessibile standard, trasparente o argentato, con tappo tipo "Vitop" da 1 a 30 litri, con regolazione altezza della forcella di sostegno, esclusivamente per i sacchetti sopra elencati.
- Possibilità di riempimento contenitori no bag in box da 1 a 99 litri con apposito adattatore in dotazione.
- Adattatore in acciaio inox con portagomma (falso bag in box/ chip di lavaggio) da applicare alla forcella per il lavaggio e la sanificazione della macchina.
- Sistema semiautomatico di estrazione ed inserimento tappo.
- Estrazione automatica dell'aria dai sacchetti prima del riempimento e regolazione del livello di vuoto desiderato.
- Possibilità di iniezione azoto prima e dopo il riempimento.
- Valvola pneumatica in acciaio inox.
- Pistone Pneumatico bloccaggio testa di riempimento.
- Elettropompa autoadescante a girante in gomma con by-pass, motore HP 1,5.
- Sostegno regolabile per appoggio scatola di cartone.
- Carrello in acciaio inox su ruote.
- Compressore elettrico silenziato 220 V.
- Produzione: tempo di confezionamento di un sacchetto da 3 Litri 10 secondi circa; da 5 Litri 15 secondi circa (tempistiche variabili a seconda della velocità dell'operatore).
- Alimentazione 220 V. 50 Hz.
- Misure 600 x 820x 1600 mm. Peso Kg. 110 circa.



MONTANARO F. L L I SRL

Officina Macchine Enologiche

Via Cav. Ottavio Riccadonna, 218 - 14053 – CANELLI (AT)

Tel. E Fax. +39 0141 823611

E-mail: info@montanarofratelli.com

Internet: www.montanarofratelli.com

COD. FISCALE E P. IVA 01429500059
NR. REG. IMPR CC.I.AA AT: 01429500059

SEMIAUTOMATIC FILLING BAG IN BOX





MONTANARO F. L L I SRL

Officina Macchine Enologiche

Via Cav. Ottavio Riccadonna, 218 - 14053 – CANELLI (AT)

Tel. E Fax. +39 0141 823611

E-mail: info@montanarofratelli.com

Internet: www.montanarofratelli.com

COD. FISCALE E P. IVA 01429500059

NR. REG. IMPR CC.I.AA AT: 01429500059



Automatic programming and storage of filling volumes by display with “touch screen” digital control panel, with possibility for to save the filling’s programs.

- Electromagnetic flow meter Burkert.
- Possibility of filling standard flexible bag, transparent or silver, with “Vitop” type cap from 1 to 30 liters, with height adjustment of the support fork, exclusively for the bags listed above.
- Possibility of filling no bag in box containers from 1 to 99 liters with the special adapter supplied.
- Stainless steel adapter with hose connection (fake bag in box / washing chip) to be applied to the fork for washing and sanitizing the machine.
- Semiautomatic system for extract and plug insertion.
- Automatic air extraction from bags before filling and adjusting the desired vacuum level.
- Possibility of nitrogen injection before and after filling.
- Stainless steel pneumatic valve.
- Pneumatic piston for filling cap locking
- Self-priming electric pump with rubber impeller and by-pass, Engine HP 1,5.
- Adjustable support for carton box support.
- Stainless steel trolley on wheels
- Electric silence compressor 220 V.
- Production: packing time of a 3 liter bag about 10 seconds; from 5 liters to about 15 seconds (timing depends on the speed of the operator).
- Power supply: 220 V. 50 Hz
- Dimensions: Length 600mm x Width 820mm x H 1600mm. Weight Kg 110 about.